

DigitalMedia 8G™ Fiber Receiver & Room Controller 100

- > DigitalMedia 8G™ Fiber receiver and display controller
- > Connects to a DM® switcher or transmitter over one multimode fiber strand^[1]
- > Supports cable lengths up to 1000 ft (300 m) using CresFiber® 8G, or 500 ft (150 m) using other multimode fiber^[1]
- > Provides one HDMI® or DVI display output^[2]
- > Handles video resolutions up to Full HD 1080p
- > Handles computer resolutions up to WUXGA
- > Handles 3D video and Deep Color
- > Handles Dolby® TrueHD, DTS-HD®, and uncompressed 7.1 linear PCM audio
- > HDCP compliant
- > Provides a 10/100 Ethernet LAN connection
- > Enables device control via CEC, IR, RS-232, and Ethernet
- > Compatible with Crestron® USB over Ethernet Extenders^[3]
- > Allows quick, easy setup and diagnostics
- > Low-profile surface mount design
- > Universal power pack included

The DM-RMC-100-S provides a simple one-box interface solution for a single display device as part of a complete Crestron® DigitalMedia™ system. It functions as a DM 8G® Fiber receiver and control interface, providing a single HDMI® output along with Ethernet, RS-232, and IR control ports. Its compact, low-profile design allows the DM-RMC-100-S to be installed discreetly behind a flat panel display or above a ceiling mounted projector. It connects to the head end or source location using a single multimode fiber strand.^[1]

DigitalMedia 8G™ Fiber

As the leader in HDMI and control system technologies, Crestron developed DigitalMedia (DM®) to deliver the first complete HD AV distribution system to take HDMI to a higher level. DigitalMedia allows virtually any mix of HDMI and other AV sources to be distributed throughout a home, office, school, or virtually any other facility. The latest generation of DM is called DigitalMedia 8G (DM 8G). Engineered for ultra high-bandwidth and ultimate scalability, DM 8G provides a true one-wire lossless transport for moving high-definition video, audio, Ethernet, and control signals over a choice of twisted pair or fiber optic cable.

DM 8G Fiber uses multimode fiber to enable signal distribution between buildings and over lengthy wire runs. DM 8G Fiber handles uncompressed Full HD 1080p video signals with support for 3D, Deep Color, and HDCP, as well as computer signals up to WUXGA. Audio capabilities include support for high-bitrate 7.1 audio formats like Dolby® TrueHD and DTS-HD Master Audio™ as well as uncompressed linear PCM. All signals are transported over one strand of multimode fiber, supporting distances up to 1000 feet (300 m) using CresFiber® 8G, or 500 feet (150 m) using other multimode fiber optic cable.^[1]



Multimedia Display Interface

A single HDMI digital AV output port is provided on the DM-RMC-100-S for connection to a display or other device. The HDMI output can also handle DVI signals using an appropriate adapter or interface cable^[2].

A single fiber strand connects the DM-RMC-100-S to a DM switcher or transmitter, transporting video, audio, control, and networking signals all through one simple SC type optical connection.^[1] Multiple DM-RMC-100-Ss may be installed to handle each display in a multiroom distribution system, all fed from a central DM-MD series switcher. Or, a single DM-RMC-100-S can be fed straight from a DM 8G Fiber transmitter, affording a simple solution for extending a computer or AV signal to a single display.

LAN Connectivity


Along with high-definition AV and control, DigitalMedia also integrates high-speed Ethernet networking for a total signal distribution solution. The DM-RMC-100-S includes a 10/100 Ethernet port, providing a convenient LAN connection for a local network device.

Embedded Device Control

The primary objective of every Crestron system is to enable precisely the control desired for a seamless user experience. The DM-RMC-100-S includes built-in RS-232, IR, and Ethernet control ports to allow programmable control of the display device connected to it. But, it can also provide an alternative to such conventional control methods by harnessing the CEC (Consumer Electronics Control) signal embedded in HDMI. Through its connection to the control system, the DM-RMC-100-S provides a gateway for controlling the display device right through the HDMI connection, potentially eliminating the need for any dedicated control wires or IR emitters.

USB Signal Extension (optional)

DigitalMedia allows for the routing of USB signals alongside video and audio. USB signal extension is enabled on the DM-RMC-100-S by adding a USB-EXT-DM USB over Ethernet Extender Module^[3].



DM-RMC-100-S – Left, Front, and Right Views

Low-Profile Installation

The DM-RMC-100-S mounts conveniently to a wall, ceiling, or other flat surface. At just one inch deep, it fits easily behind a flat panel display or above a ceiling-mounted projector. All connections and LED indicators are positioned on the sides, ensuring optimal access and visibility for a clean, serviceable installation. An array of indicators is provided for easy setup and troubleshooting.

Please refer to the DigitalMedia Resources Webpage at <http://www.crestron.com/dmresources/> for additional design tools and reference documents.

SPECIFICATIONS

Video

Input Signal Type: DM 8G® Fiber (DigitalMedia™ over one multimode fiber optic strand)^[1]

Output Signal Types: HDMI®, DVI^[2]

Formats: DM 8G Fiber & HDMI w/Deep Color & 3D, DVI, HDCP content protection support

Input Resolutions, Progressive: 640x480@60Hz, 720x480@60Hz (480p), 720x576@50Hz (576p), 800x600@60Hz, 848x480@60Hz, 852x480@60Hz, 854x480@60Hz, 1024x768@60Hz, 1024x852@60Hz, 1024x1024@60Hz, 1280x720@50Hz (720p50), 1280x720@60Hz (720p60), 1280x768@60Hz, 1280x800@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1365x1024@60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1080@24Hz (1080p24), 1920x1080@25Hz (1080p25), 1920x1080@50Hz (1080p50), 1920x1080@60Hz (1080p60), 1920x1200@60Hz, 2048x1080@24Hz, 2048x1152@60Hz, plus any other resolution allowed by HDMI up to 165MHz pixel clock

Input Resolutions, Interlaced: 720x480@30Hz (480i), 720x576@25Hz (576i), 1920x1080@25Hz (1080i25), 1920x1080@30Hz (1080i30), plus any other resolution allowed by HDMI up to 165MHz pixel clock

Output Resolutions: Matched to input

Audio

Input Signal Type: DM 8G Fiber

Output Signal Type: HDMI

Formats: Dolby Digital®, Dolby Digital EX, Dolby Digital Plus, Dolby® TrueHD, DTS®, DTS-ES, DTS 96/24, DTS-HD High Res, DTS-HD Master Audio™, up to 8ch PCM

Communications

Ethernet: 10/100 Mbps, auto-switching, auto-negotiating, auto-discovery, full/half duplex, DHCP

RS-232: 2-way device control and monitoring up to 115.2k baud with hardware and software handshaking

IR/Serial: 1-way device control via infrared up to 1.1 MHz or serial TTL/RS-232 (0-5 Volts) up to 19.2k baud

DigitalMedia: DM 8G Fiber, HDCP, EDID, CEC, Ethernet

HDMI: HDCP, EDID, CEC

NOTE: Supports management of HDCP and EDID; supports management of CEC between the connected HDMI device and a control system

Connectors

HDMI OUT: (1) 19-pin Type A HDMI female; HDMI digital video/audio output; Also supports DVI^[2]

COM: (1) 5-pin 3.5mm detachable terminal block; Bidirectional RS-232 port; Up to 115.2k baud, hardware and software handshaking support

DM-RMC-100-S DigitalMedia 8G™ Fiber Receiver & Room Controller 100

IR 1 – 2: (1) 4-pin 3.5mm detachable terminal block comprising (2) IR/Serial ports;

IR output up to 1.1 MHz;

1-way serial TTL/RS-232 (0-5 Volts) up to 19200 baud

LAN: (1) 8-wire RJ45 female, shielded;

10Base-T/100Base-TX Ethernet port

Ground: (1) 6-32 screw, chassis ground lug

DM IN MMF/SC: (1) SC female optical fiber connector;

DM 8G Fiber input;

Connects to DM 8G Fiber output of a DM switcher, transmitter, or other DM device via CresFiber® 8G fiber optic cable^[1]

24VDC 0.75A MAX: (1) 2.1 x 5.5 mm DC power connector;

24 Volt DC power input;

PW-2407WU power pack included

Controls & Indicators

HDMI OUT: (1) green LED, indicates video signal presence at the HDMI output

LAN: (2) LEDs, green LED indicates Ethernet link status, amber LED indicates Ethernet activity

DM IN: (1) green LED, indicates DM link status

RESET: (1) miniature recessed pushbutton, for hardware reset

SETUP: (1) red LED and (1) miniature recessed pushbutton, for Ethernet setup

24VDC: (1) green LED, indicates operating power supplied via local power pack

Power Requirements

Power Pack: 0.75 Amps @ 24 Volts DC;

100-240 Volts AC, 50/60 Hz power pack, model PW-2407WU included

Environmental

Temperature: 32° to 104°F (0° to 40°C)

Humidity: 10% to 90% RH (non-condensing)

Heat Dissipation: 61 BTU/Hr

Enclosure

Chassis: Metal, black finish, with (2) integral mounting flanges, vented top and bottom

Mounting: Freestanding, surface mount, or attach to a single rack rail

Dimensions

Height: 6.09 in (155 mm)

Width: 5.63 in (143 mm)

Depth: 1.02 in (26 mm)

Weight

14.7 oz (416 g)

MODELS & ACCESSORIES

Available Models

DM-RMC-100-S: DigitalMedia 8G™ Fiber Receiver & Room Controller 100

Included Accessories

PW-2407WU: Wall Mount Power Pack 24VDC, 0.75A, Universal (Qty. 1 included)

Available Accessories

CRESFIBER8G-NP: CresFiber® 8G Multimode Fiber Optic Cable, 50/125 x4 breakout, non-plenum

CRESFIBER8G-P: CresFiber® 8G Multimode Fiber Optic Cable, 50/125 x4 breakout, plenum

CRESFIBER-CONN-SC50UM-12: Connectors for CresFiber® 8G Multimode Fiber Optic Cable, SC 50µm, 12-Pack

CRESFIBER-TK: CresFiber® Termination Kit (AFL Telecommunications™)

CRESFIBER-SINGLE-SC-P: CresFiber® Simplex Fiber Optic Cable Assembly, 50/125, SC, Plenum

CBL Series: Crestron® Certified Interface Cables

MP-WP: Media Presentation Wall Plates

MPI-WP Series: Media Presentation Wall Plates - International Version

CNSP-XX: Custom Serial Interface Cable

IRP2: IR Emitter Probe w/Terminal Block Connector

USB-EXT-DM: USB over Ethernet Extender with Routing

Notes:

1. The maximum cable length for DigitalMedia 8G Fiber (DM 8G Fiber) is 1000 ft (300 m) using Crestron **CRESFIBER8G** multimode fiber optic cable, or 500 ft (150 m) using Crestron legacy **CRESFIBER**, Crestron **CRESFIBER-SINGLE-SC**, or third-party OM3 simplex multimode fiber optic cable. Refer to the [Crestron DigitalMedia Design Guide, Doc. #4546](#) for complete system design guidelines. All wire and cables are sold separately.
2. The HDMI output requires an appropriate adapter or interface cable to accommodate a DVI signal. **CBL-HD-DVI** interface cables are available separately.
3. **USB-EXT-DM** USB over Ethernet Extender Modules are sold separately. Refer to the [USB-EXT-DM](#) spec sheet for more information.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, the Crestron logo, CresFiber, DigitalMedia, DigitalMedia 8G, DM, and DM 8G are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Dolby and Dolby Digital are either trademarks or registered trademarks of Dolby Laboratories in the United States and/or other countries. DTS, DTS-HD, and DTS-HD Master Audio are either trademarks or registered trademarks of DTS, Inc. in the United States and/or other countries. HDMI and the HDMI Logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2015 Crestron Electronics, Inc.

DM-RMC-100-S

DigitalMedia 8G™ Fiber Receiver & Room Controller 100

